



### **Technical Support**

If you need technical support with your SSL product or have questions about its use, please contact us:

**805.751.4855**



**Congratulations on your purchase of this Sound Storm Laboratories (SSL) SS Series Subwoofer. SSL takes great pride in producing products that look great, sound great, and stand up to the daily rigors applied by audio enthusiasts around the world. We appreciate your confidence and support and we thank you for choosing SSL.**



**SS10 10" (25 cm) Subwoofer**

- *Single 4 Ω Voice Coil*
- *600 W Peak Power Handling*
- *1.5"(38 mm) High Temperature Voice Coil*
- *Foam Surround*

### Product Specifications

Impedance	4 Ω
Fs	32.3 Hz
Qts	0.505
Qms	4.82
Qes	0.564
Vas	2.545 cu ft. (72.06 liters)
Xmax	12 mm
Sensitivity (1 W/ 1 m)	88 dB
Peak Power Handling	600 W
Mounting Depth	4-1/8" (124 mm)
Cutout Diameter	9-1/8" (232 mm)

### Enclosure

A sealed enclosure is recommended. Below you will find the dimensions to make the enclosure to suit the parameters, it has been designed for maximum output while retaining great sound quality. The dimensions have already accounted for the volume displacement of the subwoofer, and using 3/4" (19mm) MDF. All dimensions are external. It has an internal volume of 1.15cu ft. (32.56 liters)

### Dimensions:

- Length (L) : 17" (431.8mm)
- Width (W) : 10" (254 mm)
- Height (H) : 12" (304.8mm)
- Cutout Diameter: 9-1/8" (2332 mm)

